

LaserFocusWorld®

International Resource for Technology and Applications in the Global Photonics Industry

Optics, Coatings, Mechanics, Motor Stages

- HOME
- BROWSE BY TOPIC
- BUYERS GUIDE
- PRODUCTS
- BUSINESS CENTER
- RESOURCES
- EVENTS
- VIDEO
- MOBILE
- JOBS

[Home](#) > [More Lasers & Sources Articles](#) > **SOLID-STATE DEEP UV EMITTERS/DETECTORS: Zinc oxide moves further into the ultraviolet**

SOLID-STATE DEEP UV EMITTERS/DETECTORS: Zinc oxide moves further into the ultraviolet

10/10/2013


Recent breakthroughs in the alloying of zinc oxide (ZnO) with magnesium (Mg) could offer an alternative to (Al)GaN-based emitters/detectors in the deep UV with reduced lattice and efficiency issues.

DAVID J. ROGERS, PHILIPPE BOVE, ERIC V. SANDANA, FERECHEH HOSSEINI TEHERANI, RYAN MCCLINTOCK, and MANIJEH RAZEGHI

Zinc oxide (ZnO) is a remarkable, multifunctional semiconducting material with a direct, wide bandgap energy ($E_g \sim 3.4$ eV), intrinsically high transparency over the whole visible range, and a resistivity that can be tuned from semi-insulating right through



Sponsor Information



LASER FOCUS WORLD MAGAZINE

[Read the Current Issue](#)

[Read Past Issues](#)

to semi-metallic by doping.¹ It also presents one of the highest piezoelectric responses of any semiconductor and has a relatively high thermoelectric figure of merit. Moreover, it has been judged to be biocompatible and has been approved for human consumption (in products such as vitamin pills) by the U.S. Food and Drug Administration.

These distinctive properties have led to a number of industrial applications for ZnO. A recent Nanomarkets (Glen Allen, VA) study estimated that the ZnO-based optoelectronics market was already worth over half a billion dollars in 2010 and forecast to grow to more than 2.3 billion dollars by 2017, at which point over 65% of the market is to be made up of emerging applications: predominantly photovoltaics, displays, light-emitting diodes (LEDs), and sensors (gas, ultraviolet [UV] light, and biological).

In photovoltaics, ZnO is currently displacing indium tin oxide for use as a transparent conducting electrical contact due to recent improvements in conductivity obtainable with aluminium-doped ZnO, combined with processing, cost, and toxicity advantages.²

For display applications, the greatly superior electron mobilities and current on/off ratios that can be obtained with ZnO-based transparent thin film transistors have opened up the potential for replacing amorphous silicon select field-effect transistors in both active-matrix organic LED and liquid-crystal-based displays/screens.

ZnO benefits

The emerging potential of ZnO for UV emitter and detector applications is the result of a long, concerted, and fruitful R & D effort that culminated in more than 7000 publications in 2012 (see Fig. 1). In the early years, the research focused principally on the crystal structure and the basic physical/optical properties. The upturn in output from the early 1990s was most probably triggered by the burgeoning technical and commercial success of gallium nitride (GaN) in optoelectronic devices.

[Subscribe to Laser Focus World Magazine](#)

[Subscribe to Laser Focus World Newsletters](#)

BWTEK INC.
Your Spectroscopy Partner

The World Leader in
Portable Raman Spectrometers



BUYERS GUIDE

- [Laser Sources](#)
- [Laser Specification Tables](#)
- [Applied Optical Systems](#)
- [Optical Coating & Fabrication](#)
- [Optical Test & Measurement Equipment](#)
- [Fiber-optic Components](#)
- [Laser Systems Parts & Accessories](#)
- [Detectors & Accessories](#)
- [Materials & Substrates](#)
- [Products & Services](#)

[Click here](#) to have your products listed in the Laser Focus World Buyers Guide.

TOPIC INDEX

[View Laser Focus World articles by topic,](#)




FIGURE 1. The number of annual publications vs. year, according to a search of the www.scopus.com database for the term "ZnO" in the abstract, title, or keywords.

A link was made between ZnO and GaN because they are very similar materials with the same wurtzite crystal structure, comparable lattice-constants/bandgaps, and high cohesive-energies/melting points (see table). There are some important differences, however. In particular, ZnO is considered to be a potentially superior material for use in LEDs and laser diodes because of its much larger exciton binding energy (60 meV) compared to 21 meV for GaN (thermal energy at room temperature is about 25 meV). This means that we can expect brighter and more robust excitonic-based ZnO emitters.

A comparison of selected properties of ZnO and GaN

Materials	Crystal structure	Lattice parameters		Room-temperature bandgap	Cohesive energy	Melting point	Exciton-binding energy
		a (Å)	c (Å)	(eV)	(eV)	(°C)	(meV)
ZnO	Wurtzite	3.249	5.207	3.37	1.89	1975	60
GaN	Wurtzite	3.189	5.185	3.39	2.24	2500	21

Furthermore, wet etching is possible for ZnO with nearly all dilute acids and alkalis (greatly simplifying device processing), whereas GaN requires hydrofluoric (HF) acid or plasma etching. Zinc oxide is also relatively abundant (unlike Ga), so ZnO cost is low. Finally, high-quality ZnO films can be grown more readily on mismatched substrates (due to the particularly compliant nature of ZnO), and bulk ZnO substrates have better availability than

A-Z

VIDEO LIBRARY

[View the Laser Focus World video library](#)

ARTICLE ARCHIVE

[View Laser Focus World past articles now.](#)

TOPIC CENTERS

- [Spectroscopy](#)
- [Defense & Security - NEW TOPIC](#)
- [Detectors and Imaging](#)
- [Fiber Optic Components & Systems](#)
- [Lasers & Sources](#)
- [Optical Components & Systems](#)
- [Positioning, Support & Accessories](#)
- [Photonics Education](#)
- [Photonics Business](#)
- [Science and Research](#)
- [Software](#)
- [Test & Measurement](#)

SOCIAL ACTIVITY

Everyone	Friends	Me
Recent user activity on Laser Focus World:		
	ROBERT Dyrmishi commented on: Hollow-core dielectric-coated fibers deliver mid-IR laser light : "To... Thu Sep 26 2013	
	Darin McDonald commented on: Laser-fused dentures now half the cost of milled versions : "Lichtenfe... Tue Sep 24 2013	
	Danial Louis commented on: BUSINESS FORUM: Photonics: Technology, business, and everything else ... Tue Sep 17 2013	
	Jason Sapan commented on: Holographic display fiction : "Almost half a century has passed since ... Tue Aug 20 2013	
	Commented on: Raytheon wins 2011 Herschel Award for silicon p-i-n detectors - Laser Focus World Wed Aug 14 2013	
	Commented on: Lumen Dynamics UV LED curing system integrates into production lines - Laser Focus World Mon Aug 12 2013	
	Oded Raz commented on:	

their GaN equivalents.

Another upturn in ZnO-related publications after the year 2000 can be associated with several key findings, including the demonstration of stimulated excitonic emission at temperatures higher than 550 K, reports of *p*-type doping, and the emergence of ZnO as an important nanomaterial (see Fig. 2). A Thomson-Reuters market survey, published in 2010, recorded more publications dedicated to nanostructured ZnO than to carbon nanotubes. This is primarily due to the multifunctional nature of ZnO, the ease of fabricating nanostructures by various techniques (including wide-area, low cost chemical growth), and the extremely large family of nanostructure types that can be obtained.




FIGURE 2. A scanning electron microscope (SEM) image shows two facing surfaces of silicon wafers coated with commercially available arrays of self-forming, vertically oriented ZnO nanostructures grown by pulsed laser deposition.

LEDs and lasers

In spite of the potential of ZnO-based LEDs, their commercialization has been hampered by issues of simultaneously reducing intrinsic *n*-type doping and incorporating/activating sufficient acceptors. The native donor compensation is usually associated with defects inherent to oxygen-deficient ZnO (O vacancies and Zn interstitials) plus unintentional impurity incorporation (hydrogen, in particular).

Since 1999, however, there have been a multitude of reports of *p*-type doping.³ These efforts have used a wide range of growth

techniques, substrates, and acceptor doping approaches with a variety of group-I, -IV, and -V elements, co-doping, and impurity/defect complexes, respectively. The most commonly reported acceptor dopants are nitrogen (N), arsenic (As), phosphorus (P), and antimony (Sb). And native acceptor defect doping (with Zn vacancies and O interstitials) has been targeted through oxidant-rich growth.

There have been many demonstrations of blue and near-UV ZnO homojunction LEDs as well, and state-of-the-art performance (70 μW at 30 mA) can be compared to that of GaN-based LEDs in the mid-1990s.⁴ Issues to be addressed include an asymmetry in the n - and p -type carrier concentrations, relatively low p -type mobilities, and poor electrical contacts.

There have also been many reports of low-threshold, high-gain UV lasing from ZnO-based materials and devices under optical pumping, including room-temperature UV photonic crystal lasing and random lasing from self-forming laser cavities.⁵ What's more, patterned ZnO-based microcavities have shown promise for use as low-threshold surface-emitting polariton lasers. And recently, there have been reports of electrically pumped ZnO lasers, although relatively low doping levels limit the performance.

Deep-UV emitters and detectors

Alloys of GaN with aluminum ($\text{Al}_x\text{Ga}_{1-x}\text{N}$) have been widely explored for emission and detection of UV light (see Fig. 3).⁶ This material system is plagued by several problems, however, including large dislocation densities, low n -type and p -type doping efficiency, low conductivity, and lattice/thermal expansion mismatches that lead to cracking. As a result, efficiency falls off dramatically with increasing Al content, and there has been limited success in demonstrating solar-blind UV photodetectors (SBPDs; i.e., in the 240–290 nm range) with low background signals and high quantum efficiencies.




FIGURE 3. E_g vs. lattice constant is shown for wurzite (Al,In)GaN and (Mg,Cd)ZnO. UV bandgap engineering of ZnO (up to 10.6 eV) can also be achieved effectively by alloying with BeO. There are toxicity and handling issues in this case, however.

Alloys of ZnO with magnesium ($Mg_xZn_{1-x}O$) have been explored as an alternative to (Al)GaN and are now commercially available.⁷ The Mg ion has a similar radius to that of Zn, so there are less strain and efficiency drop-off concerns than for (Al)GaN.

The commercialization of (Mg)ZnO-based UV devices will most probably begin with detector applications rather than emitters because photodetector technologies that do not require p -type doping (such as photoconductors, Schottky diodes, metal-semiconductor-metal devices, and surface acoustic wave devices) have already been demonstrated.

UV photodetectors are envisioned for detection of weak UV signals in applications such as flame/chemical/biological-agent detection, UV astronomy, next-generation missile warning/guidance systems, hostile fire identification, environmental monitoring, and non-line-of-sight communications. To minimize false alarms and background clutter, many of these systems operate in the [solar-blind SB portion of the UV spectrum](#).

While (Al)GaN-based detectors work well in the near-UV, current commercial SB detection systems are usually based on photomultiplier tubes (PMTs) with cesium telluride (Cs_2Te) photocathodes. These have a detection tail out to 325 nm, which overlaps with the solar UV spectrum, making these sensors not truly blind to solar background radiation, however. Thus filters and complex optics are usually required to achieve true SB status. State-of-the-art PMT detectors have a peak

detective quantum efficiency of 15%. In addition, the high-voltage vacuum tubes are bulky, fragile (mechanically and electrically—high flux can physically damage the internal electron multiplication grids), expensive, and require high operating voltages.

Solid-state SBPDs promise performance, size, and cost advantages compared to PMTs. Such arrays have no moving parts, are intrinsically radiation hard, and potentially offer higher quantum efficiency, higher selective sensitivity, extended lifetimes, lower noise, and lower-power requirements. Direct-gap semiconductors also offer very sharp cutoffs (<10 nm per decade) compared to existing photocathodes (around 25 nm per decade). This allows them to be made significantly more solar blind while maximizing the capture of the SB portion of the UV emission.

For fabricating (Mg)ZnO-based SBPDs, Mg content should be at least 45 at %, but many studies have found that phase segregation of rock-salt phase MgO appears when Mg content is over 36 at %. Recently, however, single-phase wurtzite layers with Mg concentrations over 49 at % were prepared through strain engineering at the substrate interface by means of buffer layers (ZnO and strontium tin oxide—SrTiO₃—or bulk ZnO substrates).⁸⁻¹⁰

Furthermore, it has been reported that Mg alloying facilitates the task of *p*-type doping. Two main reasons are put forward for this. First, the addition of Mg in ZnO shifts the conduction band edge to a higher energy, which increases the activation energy of the donor states and thereby reduces the *n*-type background electron concentration.¹¹ Second, the Zn vacancy (acceptor) concentration has been observed to increase with Mg concentration, which boosts the increment of hole concentration and *p*-type conduction.¹² Another intrinsic advantage compared to (Al)GaN is the even greater resistance of (Mg)ZnO to ionizing radiation and high-energy particles.

Current (Mg)ZnO-based SBPD research has recently extended to nanostructures. These offer higher crystal quality, non-polar core-shell junctions, better compatibility with silicon, very wide-area low-temperature chemical growth on mismatched substrates, an advantageous size-related blue shift, reduced device processing (inter-digit patterning can be circumvented), plus intrinsic antireflection advantages. Indeed, ZnO

nanowire-based UV PDs have been widely reported in the literature, and such devices have already shown larger gain bandwidth compared to bulk devices, very high photoconductive gains (up to approximately 10^8), single-photon sensitivity, and Schottky barrier contacts, which eliminate long transients and thereby boost response speed.

(Al)GaN-based deep-UV solid-state emitters and detectors have shown cracking and disappointing efficiencies, so (Mg)ZnO-based alternatives are being investigated as possible substitutes.

This effort has been boosted by recent advances in strain engineering at the substrate interface, which have allowed stabilization of single-phase wurtzite (Mg)ZnO with up to 49% Mg.

Moreover, the *p*-type doping issues of unalloyed ZnO (associated with native donor defect compensation and insufficient acceptor concentrations) are significantly reduced in (Mg)ZnO because of the higher activation energy of the donor state and the increase in zinc vacancy acceptor density with Mg content. For detector applications, *p*-type doping is not a requisite, however, and nanostructured (Mg)ZnO-based devices have already demonstrated the promise of improved performance, simplified processing, wider areas, and lower cost compared to their thin-film (Al)GaN-based equivalents.

ACKNOWLEDGEMENTS

The authors wish to thank Carlos Lee (director general of the European Photonics Industry Consortium; Paris, France) for his support in this work, professor Seong-Ju Park of the Gwangju Institute of Science & Technology (GIST; Gwangju, Korea) for useful exchanges on the state-of-the-art in *p*-type ZnO doping and Professor Jose-Luis Pau of Universidad Autónoma de Madrid (Madrid, Spain) for discussions on the state-of-the-art in nanostructured UV photodetectors.

REFERENCES

1. D. J. Rogers et al., *Proc. SPIE*, 7605, 76050K-1 (2010).
2. D. J. Rogers and F. Hosseini Teherani, *Encyclopedia of*

Materials Science & Technology, 1–5, Elsevier, Oxford, England (2010).

3. J.-C. Fan et al., *Prog. Mater. Sci.*, 58, 874 (2013).
4. K. Nakahara et al., *Appl. Phys. Lett.*, 97, 013501 (2010).
5. A.-S. Gadallah et al., *Appl. Phys. Lett.*, 102, 171105 (2013).
6. M. Henini and M. Razeghi, *III-Nitride Optoelectronic Devices*, Chapter 1, Elsevier, England (2004).
7. D. J. Rogers et al., *Proc. SPIE*, 8626, 862601 (2013).
8. S. Fujita et al., *Phys. Status Sol. B*, 241, 599 (2004).
9. W. Yang et al., *Appl. Phys. Lett.*, 82, 3424 (2003).
10. Q. Zheng et al., *Appl. Phys. Lett.*, 98, 221112 (2011).
11. P. Wang et al., *Appl. Phys. Lett.*, 89, 202102 (2006).
12. Y. F. Lee et al., *Appl. Phys. Lett.*, 91, 232115 (2007).

David J. Rogers is CTO, **Philippe Bove** is COO, **Eric V. Sandana** is an engineer, and **Ferechteh Hosseini Teherani** is CEO at Nanovation, 8 route de Chevreuse, Chateaufort, 78117 France; email: rogers@nanovation.com; www.nanovation.com. **Ryan McClintock** is an associate professor and **Manijeh Razeghi** is Walter P. Murphy professor of Electrical and Computer Engineering and director at the Center for Quantum Devices at Northwestern University, 633 Clark St., Evanston, IL 60208; www.northwestern.edu.

0

Facebook

2

Twitter

1

LinkedIn

[More Laser Focus World Current Issue Articles](#)
[More Laser Focus World Archives Issue Articles](#)

POST A COMMENT

Easily post a comment below using your LinkedIn, Twitter,

Google or Facebook account.

RELATED ARTICLES

[iLuma Photonics releases pulsed fiber laser](#)

[\\$5.6M investment in ID Quantique to advance quantum communications](#)

[Sapphire substrate market to nearly triple as demand booms for covers in smartphones](#)

[ADVANCES IN COMMUNICATIONS: New FSO provides reliable 10 Gbit/s and beyond backhaul connections](#)

EDITORS' PICKS

[\(SLIDE SHOW\) Supercontinuum sources span the spectrum](#)

[DELICAT LIDAR system alerts pilots to air turbulence ahead](#)

[\(SLIDE SHOW\) The smartphone as photonic instrument](#)

[Study finds that light wavelength impacts flavor, scent of plants and fruits](#)

MOST POPULAR ARTICLES

[SWEPT-WAVELENGTH LASERS: Akinetic all-semiconductor swept lasers boost OCT image quality](#)

[ORGANIC LIGHT-EMITTING DIODES: Platinum-rich polymer could enable truly white OLED](#)

[ADVANCES IN COMMUNICATIONS: New FSO provides reliable 10 Gbit/s and beyond backhaul connections](#)

[MEDICAL APPLICATIONS OF FIBER-OPTICS: Optical fiber sees growth as medical sensors](#)

[MOLECULAR IMAGING: QCLs enable mid-IR spectral image-based molecular detection](#)

DETECTORS AND IMAGING

BIOMIMETICS: Polymer-chlorophyll solid could be foundation for photonic devices

IR IMAGING: SWIR cameras spot unwanted activities through fog and at night

MOLECULAR IMAGING: QCLs enable mid-IR spectral image-based molecular detection

[More Detectors and Imaging](#)

LASER & SOURCES

iLuma Photonics releases pulsed fiber laser

\$5.6M investment in ID Quantique to advance quantum communications

Sapphire substrate market to nearly triple as demand booms for covers in smartphones

ADVANCES IN COMMUNICATIONS: New FSO provides reliable 10 Gbit/s and beyond backhaul connections

BIOMIMETICS: Polymer-chlorophyll solid could be foundation for photonic devices

[More Laser & Sources](#)

OPTICAL COMPONENTS & SYSTEMS

Luminit forms holographic Security Microstructure Group

Photonics, ghosts, and orbs

\$5.6M investment in ID Quantique to advance quantum communications

Gooch & Housego acquires Spanoptic, maker of precision optics

Infrared focus assembly contract from Lockheed goes to LightWorks

[More Optical Components & Systems](#)

SOFTWARE

[CRAIC Technologies releases image analysis software](#)

[Specim Spectral Imaging releases hyperspectral sensing software](#)

[Lumerical introduces photonic design software](#)

[More Software](#)

TEST & MEASUREMENT

[Zygo introduces a profiler for 3D imaging and measurement](#)

[SWEPT-WAVELENGTH LASERS: Akinetic all-semiconductor swept lasers boost OCT image quality](#)

[MOLECULAR IMAGING: QCLs enable mid-IR spectral image-based molecular detection](#)

[Top Photonics News: New resources from Laser Focus World-- October 11, 2013](#)

[SPECTROSCOPY: VCSELs benefit TDLAS combustion measurements](#)

[More Test & Measurement](#)

RECENT ARTICLES

[Texas Tech physicist's spectroscopic camera captures day-old supernova](#)

[Luminit forms holographic Security Microstructure Group](#)

[iLuma Photonics releases pulsed fiber laser](#)

[Zygo introduces a profiler for 3D imaging and measurement](#)

FROM THE ARCHIVES

Quantum-dot VCSELs can emit anywhere in the visible spectrum

04/30/2012

Terahertz microchip could let cell phones see through walls

04/27/2012

Laser-based 3D nozzle quality test from Fraunhofer ILT improves laser material deposition

04/26/2012

FIBER LASERS: Fiber lasers: The state of the art

04/01/2012

DIODE-PUMPED SOLID-STATE LASERS: Laser dazzlers are deployed

03/01/2012

OPTICAL DATA STORAGE: Holographic data storage uses volumetric crystal media

02/07/2012

Sandia's laser-guided bullet prototype can hit small targets a mile away

02/02/2012

FIBER OPTIC COMPONENTS & SYSTEMS

iLuma Photonics releases pulsed fiber laser

ADVANCES IN COMMUNICATIONS: New FSO provides reliable 10 Gbit/s and beyond backhaul connections

PHOTONIC FRONTIERS: ELECTRONIC DISPERSION MANAGEMENT: Digital electronics clean up dispersion in high-speed fiber systems

OPTOFLUIDICS: Optofluidic light switch enables reconfigurable solar lighting

Top Photonics News: New resources from Laser Focus World-- October 11, 2013

[More Fiber Optic Components & Systems](#)

POSITIONING, SUPPORT & ACCESSORIES

[Gbit/s and beyond backhaul connections](#)

[PHOTONIC FRONTIERS: ELECTRONIC DISPERSION MANAGEMENT: Digital electronics clean up dispersion in high-speed fiber systems](#)

[OPTOFLUIDICS: Optofluidic light switch enables reconfigurable solar lighting](#)

[Top Photonics News: New resources from Laser Focus World-- October 11, 2013](#)

[More Positioning, Support & Accessories](#)

SCIENCE AND RESEARCH

[Texas Tech physicist's spectroscopic camera captures day-old supernova](#)

[\\$5.6M investment in ID Quantique to advance quantum communications](#)

[BIOMIMETICS: Polymer-chlorophyll solid could be foundation for photonic devices](#)

[Metamaterial inventor Sir John Pendry awarded the Julius Springer Prize for Applied Physics 2013](#)

[Top Photonics News: New resources from Laser Focus World-- October 11, 2013](#)

[More Science and Research](#)

SPECTROSCOPY

[Texas Tech physicist's spectroscopic camera captures day-old supernova](#)

[Top Photonics News: New resources from Laser Focus World-- October 11, 2013](#)

[ORGANIC LIGHT-EMITTING DIODES: Platinum-rich polymer could enable truly white OLED](#)

[SPECTROSCOPY: VCSELs benefit TDLAS combustion measurements](#)

[Photonics is edgy](#)

[More Spectroscopy](#)





TOPICS

- [Spectroscopy](#)
- [Defense & Security](#)
- [Detectors and Imaging](#)
- [Fiber Optic Components & Systems](#)
- [Lasers & Sources](#)
- [Optical Components & Systems](#)
- [Positioning, Support & Accessories](#)
- [Photonics Education](#)
- [Photonics Business](#)
- [Science and Research](#)
- [Software](#)
- [Test & Measurement](#)

ABOUT US & SUPPORT

- [Laser Focus World Magazine](#)
- [Contact Us](#)
- [About Us](#)
- [Advertising](#)
- [Subscribe](#)
- [Login](#)
- [Register](#)
- [RSS](#)

RESOURCES

- [Webcasts](#)
- [White papers](#)
- [Editorial Digests](#)
- [Video](#)
- [Blogs](#)
- [Events](#)
- [PennWell Events](#)
- [PennWell Websites](#)
- [Strategies Unlimited](#)

SECTOR PUBLICATIONS

- [Laser Focus World](#)
- [Laser Focus World Japan](#)
- [Laser Focus World China](#)
- [Industrial Laser Solutions](#)
- [Industrial Laser Solutions China](#)
- [Industrial Laser Solutions Japan](#)
- [BioOptics World Magazine](#)

STAY CONNECTED

- [Twitter](#)
- [Facebook](#)
- [Linked In](#)